

Silkolene®

SILKOLENE SCOOTER GEAR OIL 80W-90 Advanced transmission gear oil

Description

SILKOLENE SCOOTER GEAR OIL 80W-90 is a high quality advanced gear oil based on highly refined mineral base oils and a high performance additive system providing outstanding transmission and gear protection over a wide range of operating conditions.

SILKOLENE SCOOTER GEAR OIL 80W-90 is packed in an easy-to-use one-shot 125ml tube, making it easy to use and minimising waste.

Application

FUCHS SILKOLENE SCOOTER GEAR OIL 80W-90 has been formulated specifically for use in scooters and mopeds and is suitable for use in all scooters where an API GL-4 SAE 90, 85W-90 or 80W-90 is specified.

Advantages

- Excellent wear protection
- Multigrade viscosity gives good performance over a wide temperature range
- Easy to use one-shot tube
- Gives outstanding lubrication performance and efficient power transmission, ensuring total reliability and minimal transmission noise

Specifications

- API GL4

Product Information



Further Information

Typical Data: SILKOLENE SCOOTER GEAR OIL 80W-90

Characteristics	Unit		Test Method
SAE Rating - Gearbox		80W-90	
Specific gravity st 15°C		0.899	IP160
Kinematic Viscosity @ 40°C	mm ² /s	151.2	IP71
Kinematic Viscosity @ 100°C	mm ² /s	15.0	IP71
Viscosity Index (VI)		99	IP226
Pour point	°C	-33	IP15

Reviewed 21/04/2020 AB

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.